



Climacell *Eco + Evo*



Patented Forced Air Convection
Shelf Life & Climate Chambers



CLIMACELL® stability test chambers are designed to create exact reproducible simulations of a wide range of environmental conditions through precise control of temperature and humidity.

CLIMACELL® test chambers are suitable for ICH Q1A stability testing of drug products and substances, material quality and durability testing, and shelf-life studies. The CLIMACELL® also meets the requirements for ICH Q1B photostability studies when equipped with the EVO advanced controller and fully programmable fluorescent shelf lighting.



Food & beverage science stability testing of food, beverages and packaging including shelf-life studies



Simulating environmental conditions for agricultural applications; germination, green plant growth, plant tissue culture, crops, and fruits



QA/QC laboratory microbiological studies



ECO Controller

3" LCD display

Fuzzy Logic algorithm constantly monitors chamber conditions and continuously optimizes parameters.

(9) programs with (8) segments each for varying loads and parameters

Audible & visual alarms – temperature, time & humidity

FDA CFR 21 Part 11 compliant with addition of Warmcomm 4.0F software

USB flash & device, RS232 & optional Ethernet port

Integrated USB 30-day data logger for temperature measurement & recording

50mm (2") port



EVO Controller

5.7" LCD touch display

Fuzzy Logic algorithm constantly monitors chamber conditions and continuously optimizes parameters.

(100) programs with (100) segments each for varying loads and parameters

Audible & visual alarms – temperature, time & humidity

FDA CFR 21 Part 11 compliant with addition of Warmcomm 4.0F software

USB device, RS232 & optional Ethernet port

Integrated SD card 30-day data logger & multi-level secure user authentication

50mm (2") port

Temperature Range:

0°C up to 100°C (10°C up to 95°C with humidity)

- -10°C min. temperature option available on ECO units
- -20°C min. temperature option available on EVO units

Humidity Control:

ECO 10% up to 95% – controlled in 1% increments

EVO 10% up to 98% – controlled in 1% increments

Chamber Volumes:

111 (4 ft³) • 222 (8 ft³) • 404 (14.3 ft³) • 707 (25 ft³) • 1212 (43 ft³)

Chamber Construction:

- AISI 304 stainless steel chamber (AISI 316 SS option available)
- Double wall, seamless main chamber & removeable inner chamber

Electrical Data:

230V 50/60Hz

Optional Programmable Lighting:

- VIS & UV fluorescent lighting
- VIS LED shelf and door lighting
- Light intensity controlled in 1% increments



Optional Equipment:

- AISI 316 stainless steel chamber
- 160°C sterilization cycle (EVO only)
- Access ports 25 (1"), 50 (2"), 100 (4") mm
- Ethernet communication port
- Rolling carts for 111 & 222 models
- Door sensor and alarm
- Automatic and key door lock
- Warmcomm data acquisition software:
 - ✓ 4.0B – Receive data
 - ✓ 4.0P – Receive data and control the device
 - ✓ 4.0F – FDA 21 CFR part 111 compliant
- BMS – Building monitoring alarm contact
- Flexible PT 100 sensor
- Stainless steel exterior
- Interior light
- Water-proof socket 230V
- IQ / OQ protocols with 9pt temperature mapping

Climacell ECO/EVO Technical Data		Model	111	222	404	707	1212
Interior Dimensions Chamber: AISI 304 stainless steel (AISI 316 stainless steel option available)	Volume	ft ³	3.9	7.8	14.3	25	43
		liters	111	222	404	707	1212
	Width	inches	21.25	21.25	21.25	37	3 x 21.25
		mm	540	540	540	940	3 x 540
	Depth	inches	14.6/15	20.5/20.9	20.5/20.9	20.5/20.9	20.5/20.9
		mm	370/380	520/530	520/530	520/530	520/530
	Height	inches	20.9/21	29.9/30.1	55.7	55.7	55.7
		mm	530/535	760/765	1415	1415	1415
Exterior Dimensions (ECO/EVO)	Width	inches	29.9/30.7	29.9/30.7	41.7/43.1	57.5/59.2	103.5/103.5
		mm	760/780	760/780	1060/1100	1460/1500	2360/2360
	Depth	inches	29.5/29.7	35.4/34.8	33.9/34.8	33.9/34.8	34.2/35.4
		mm	750/755	895/885	860/885	860/885	870/898
	Height (Legs L, Caster C)	inches	44.9L/47.8C	53.9L/57.1C	75L/74.4C	75L/74.4C	75.2L/75.6C
		mm	1140L/1215C	1370L/1450C	1905L/1890C	1905L/1890C	1905L/1921C
Shelves: Stainless Steel	Capacity: # of shelf guides in chamber side walls	Maximum #	7	10	19	19	3 x 19
		Standard #	2	2	2	2	6
Shelf Distance	Min. distance between trays	Inches	2.8	2.8	2.8	2.8	2.8
		mm	70	70	70	70	70
Useable Shelf Area	Width x Depth	Inches	20.5x13.2	20.5x19.1	20.5x19.1	36.3x19.1	20.5x19.1x3
		mm	520x335	520x485	520x485	920x485	520x485x3
Maximum Shelf Load	One Shelf	lbs	44	66.1	66.1	110.2	66.1
		kg	20	30	30	50	30
	Total Per Unit	lbs	110.2	154.3	220.5	286.6	661
		kg	50	70	100	130	300
# Outer Metal Doors			1	1	1	2	3
# Inner Glass Doors			1	1	1	2	3
Volume of Steam Space		ft ³	5.8/5.9	10.6/10.8	18.5/18.7	30.9/31	61.9
		liters	163/167	299/305	524/530	876/878	1753
Operation Temperature	From 0°C (-10°C / -20°C)	Up to °C	100	100	100	100	100
Temperature Accuracy	Distribution @ 10°C	± °C	<0.5	<0.5	<1	<1	<0.9
	Distribution @ 37°C	± °C	<0.5	<0.5	<1	<1	<0.5
	Uniformity	± °C	<0.2	<0.2	<0.3	<0.4	<0.2
Heating Time to 37°C From the Ambient Temperature		Minutes	<11	<11	<13	<13	<30
Cooling Down Time From 22°C to 10°C		Minutes	<21	<17	<19	<21	<21
Recovery Time After Door Opened for 30 s according to DIN 12880	@ 37°C	Minutes	<4	<3	<3	<6	<10
	@ 50°C	Minutes	<5	<6	<7	<6	<10
Relative Humidity (RH)	Range	%	10% - 98%	10% - 98%	10% - 98%	10% - 98%	10% - 98%
Accuracy RH (T_{CHAMBER} ≥ 21°C)	In Time	%	<2	<2	<2	<2	<2
Heat Emission	@ 37°C	W	70	63	123	148	200
CO2 Concentration (EVO Only)		%	0.1 - 20	0.1 - 20	0.1 - 20	-	-
CO2 Required Pressure (EVO Only)		Bar/PSI	0.3-0.7/5-10	0.3-0.7/5-10	0.3-0.7/5-10	-	-
Noise Level of Complete Device		dB	46	50	56	58	60
Electrical Data: ECO & EVO 0°C	Max Consumption 50/60Hz	W	2050	2200	3150	3400	3500
		A	8.9	9.6	13.7	14.8	15.2
		V	230	230	230	230	230
Electrical Data: EVO -20°C Protective system: 16A minimum	Max Consumption 50/60Hz	W	1630	1780	2115	2640	3215
		V	230	230	230	230	230
IP Code			IP20	IP20	IP20	IP20	IP20
ECO/EVO Weight	Net	lbs	229.3/242.5	297/324.1	520.3/529.1	599.6/617.3	1193/1250
		kg	104/110	135/147	236/240	272/280	541/567
	Gross	lbs	288.8/390	372.6/390	696.2/617	696.7/719	1898
		kg	131/140	169/177	270/280	316/326	861
EVO Weight -20°C	Net	lbs	264.5	331	551	639	750
		kg	120	150	250	290	340
	Gross	lbs	331	412	639	741	871
		kg	150	187	290	336	395