

Genpro ELE

Electric Pure & Clean Steam Generators



Purpose-Built for Demanding Sterile Production

The Genpro ELE is configured to support your specific production requirements, whether you need to feed a single sterilizer, serve as a centralized steam source, meet WFI-quality output standards, or support clean room humidification. Using stainless steel electric heating elements, the Genpro ELE starts up in minutes, runs only when required, and is an ideal solution for facilities where plant steam is not available. Built to your exact capacity and utility requirements, the Genpro ELE delivers tight clean steam output pressure control and steam quality you can trust, backed by a comprehensive documentation package and expert US-based field service.

- ASME pressure vessel with 316L stainless steel construction.
- Stainless steel heating elements.
- 316L stainless steel piping and valves.
- Non-proprietary components throughout.
- Capacities from 50 lbs/hr up to 1200 lbs/hr.
- Fully drainable design with automatic blowdown system.
- Allen-Bradley or Siemens PLC Controls
- Available in cGMP, laboratory, or food-grade configurations.



Biopharma

Pure and clean steam is a critical utility in pharmaceutical and biotech manufacturing, supporting equipment sterilization, aseptic filling, and sterile production environments.



CDMO

Contract manufacturers operating multiple sterilizers or pieces of process equipment rely on the Genpro ELE as a centralized pure or clean steam source, delivering consistent steam quality across every point of use.



Food

Food and beverage production relies on clean steam for sterilization-in-place, direct steam injection into food products, and sterilizing processing equipment where chemical contamination is not an option.



Beer

breweries use clean steam for keg decontamination, eliminating the chemical residues and contamination risks associated with plant steam or chemical cleaning methods.

Intelligent Controls for Precise Steam Management

Industrial-grade PLC controls continuously monitor steam pressure and temperature to maintain consistent output. Optional feedwater and steam conductivity monitoring provides an additional layer of steam quality oversight for applications requiring documented compliance.

Allen-Bradley or Siemens PLC controls maintain precise steam pressure and temperature throughout operation.

Touchscreen HMI with optional secondary panel provides intuitive real-time monitoring and control with remote operation capability.

Integrated data recording and automatic fault monitoring maintains a traceable log of system data and alerts operators to process anomalies before they affect steam quality or production.





Genpro ELE

Electric Pure & Clean Steam Generators

Models	80 PSIG
ECSG 50	50 lbs/hr
ECSG 100	100 lbs/hr
ECSG 150	150 lbs/hr
ECSG 200	200 lbs/hr
ECSG 250	250 lbs/hr
ECSG 300	300 lbs/hr
ECSG 350	350 lbs/hr
ECSG 400	400 lbs/hr
ECSG 500	500 lbs/hr
ECSG 800	800 lbs/hr
ECSG 900	900 lbs/hr
ECSG 1000	1000 lbs/hr
ECSG 1200	1200 lbs/hr

Available electric steam generator models at up to 80 PSIG steam output pressure.

Optional Equipment

- Steam sample system.
- Stainless steel, sanitary feedwater booster pump.
- Feedwater conductivity monitoring and recording.
- Steam separator for pure steam demands.
- Electropolishing of the vessel and piping.
- Block and bleed valve arrangement to drain feed line when fed with USP or WFI feedwater.
- Automatic drain valve for prolong shut down.
- Steam conductivity monitoring and recording.
- Sanitary feed water piping with sanitary components and connections.
- Pressure vessels available in pressure codes for most regions or countries.
- Voltage change for different regions or countries.

Pure Steam. No Additives. No Compromises.

The Genpro ELE is available with an optional steam separator for applications requiring pure steam output. The steam separator directs generated clean steam through a tortuous path where residual moisture and impurities are stripped and discharged to drain. When condensed and tested, the resulting pure steam meets U.S. Pharmacopeia (USP) standards and Water for Injection (WFI) requirements, making it suitable for the most demanding sterile production and life science applications.

Electric Operation Overview

Stainless steel electric heating elements are used to heat and evaporate RO or DI feedwater into pure or clean steam. As the feedwater reaches operating temperature, it evaporates and travels upward through the vessel where residual moisture is removed, producing clean, dry, saturated steam at the outlet. Concentrated feedwater and dissolved solids remaining in the vessel are automatically purged via the blowdown system, maintaining consistent feedwater quality and steam output throughout operation.

Steam Sterilizer-Autoclave Integration

The Genpro ELE is available as a standalone centralized steam source or integrated directly into a BMT USA steam sterilizer. BMT USA is one of the only manufacturers offering an integrated electric pure or clean steam generator with a vertical vessel configuration, delivering up to 400 lbs/hr output capacity with a significantly reduced facility footprint compared to traditional horizontal configurations.

